

# GAS INNOVATIONS

## MATERIAL SAFETY DATA SHEET (MSDS)

## PROPANE

### PRODUCT IDENTIFICATION

▪D.O.T. SHIPPING NAME	Propane
▪SYNONYM (S)	Liquefied Petroleum Gas, Dimethylmethane
▪D.O.T. I.D. NUMBER	UN-1978
▪D.O.T. HAZZARD CLASS	2.1 Flammable Gas
▪D.O.T. LABEL (S)	Flammable Gas
▪C.A.S. NUMBER	74-98-6
▪CHEMICAL FORMULA	C <sub>3</sub> H <sub>8</sub> or CH <sub>3</sub> CH <sub>2</sub> CH <sub>3</sub>

### PHYSICAL DATA

▪MOLECULAR WEIGHT	44.097
▪FREEZING POINT	-187.7°C, -305.9°F
▪BOILING POINT	-42.1°C, 43.7 °F
▪VAPOR PRESSURE	752 kPa (gauge), 109 psig
▪SPECIFIC VOLUME	0.531 m <sup>3</sup> /kg, 8.5ft <sup>3</sup> /lb @ 1 atm, 21.1°C
▪RELATIVE DENSITY, (air=1)	1.55 @ 1 atm, 20°C
▪SOLUBILITY IN WATER	6.5 cm <sup>3</sup> /0.1 kg water @ 1 atm, 18°C
▪DESCRIPTION	At room temperature and atmospheric pressure propane is a colorless, flammable, relatively nontoxic gas, with a characteristic natural gas odor. It is shipped as a liquefied gas under its own vapor pressure.

### FIRE AND EXPLOSION HAZARD DATA

▪FLAMMABLE LIMITS IN AIR	2.2 – 9.5 % by volume
▪AUTO-IGNITION TEMPERATURE	468°C, 874°F
▪FIRE FIGHTING PROCEDURES	The only safe way to extinguish a Propane fire is to stop the flow of gas. IF the flow cannot be stopped, let the fire burn out while cooling the cylinder and the surroundings using a water spray. Personnel may have to wear approach-type protective suits and positive pressure self-contained breathing apparatus. Firefighters' turnout gear may be inadequate.
▪ UNUSAUL HAZARDS	<ol style="list-style-type: none"><li>1. Cylinders exposed to fire may rupture with violent force. Extinguish surrounding fire and keep cylinders cool by applying water from a maximum possible distance with a water spray.</li><li>2. Flammable gases may spread from a spill after the fire is extinguished and be subject to re-ignition.</li></ol>

Date prepared: September 7, 2007

---

## HEALTH HAZARD DATA

- PERMISSIBLE EXPOSURE LIMITS
- ACCUTE EFFECTS OVEREXPOSURE
  
- CHRONIC EFFECTS OF OVEREXPOSURE

OSHA TWA 1,000 ppm (1,800 mg/m<sup>3</sup>)  
ASGIH TWA None established.

Propane is nontoxic but can act as a simple asphyxiant by displacing air. Symptoms of asphyxia include rapid respirations, dizziness and fatigue. Contact with the liquid phase or with the cold gas escaping from cylinder may cause frostbite.

None known.

---

## FIRST AID INFORMATION

- INHALATION
  
- CONTACT

Move victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Call a physician.

Treat for frostbite.

---

## REACTIVITY DATE

- STABILITY
- INCOMPATIBILITY
- HAZARDOUS DECOMPOSITION/ OXIDATION PRODUCTS
- POLYMERIZATION

( X ) Stable. ( ) Unstable.

Oxidizing material.

Carbon monoxide, carbon dioxide

(X) Will not occur ( ) May Occur

---

## SPILL OR LEAKAGE PROCEDURE

Shut off all ignition sources and ventilate the area. For controlling large flows, personnel may have to wear approach-type protective suits and self-contained breathing apparatus.

---

## PRECAUTIONS

- STORAGE RECOMMENDATIONS
  
- PERSONAL PROTECTIVE EQUIPMENT
  
- BEFORE USING THE GAS

Cylinders should be stored and used in dry, well-ventilated areas away from sources of heat or ignition. Do not store with oxidizers

1. Eye protection – Safety glasses should be worn.
2. Respiratory protection – Approved respiratory equipment must be worn when airborne concentrations exceed safe levels.
3. Skin protection – No special equipment is required. Gloves are recommended for cylinder handling.

1. Secure the cylinder to prevent it from falling or being knocked over.
2. Leak check the lines and equipment.
3. Have an emergency plan covering steps to be taken in the event of an accidental release.

Date prepared: September 7, 2007

# **GAS INNOVATIONS**

**MSDS – PROPANE  
PAGE 3 OF 3**

## **DISCLAIMER**

The information, recommendations, and suggestions herein were compiled from reference material and other sources believed to be reliable. However, the MSDS's accuracy or completeness is not guaranteed by Gas Innovations or its affiliates, nor is any responsibility assumed or implied for any loss or damage resulting from inaccuracies or omissions. Since conditions of use are beyond our control, no warranties of merchantability of fitness for a particular purpose are expressed or implied. This MSDS is not intended as a license to operate under, or recommendation to infringe on, any patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.

Date prepared: September 7, 2007